

GREAT WALL <i>Fiberglass Doors</i> by <i>FeatherLodge™</i>						
STANDARD DOOR SPECIFICATIONS:						
1-3/4 THICK			CFC FREE Injected Polyurethane Core			
3 - 4X4 HINGE LOCATIONS			LVL Stiles with closed cell 15mm PVC Cap.			
1" EDGE BORE			LVL Top Rail with closed cell 15mm PVC Cap			
Door Skin Thickness = 2mm			20" LVL Lock Block			
2-1/8 FACE BORE			LVL Bottom Rail with Closed Cell 30mm PVC Cap			
WIDTH	HEIGHT	DESIGN			DOORS PER PALLET	PALLETS PER CONTAINER
WOODGRAINED & SMOOTH SKIN						
30" /32" / 36"	80"	FLUSH			28	26
30" /32" / 36"	80"	3 PANEL DESIGNER SERIES			28	26
30" /32" / 36"	80"	6 PANEL COLONIAL			28	26
30" /32" / 36"	80"	4 PANEL COLONIAL TOP			28	26
30" /32" / 36"	80"	4 PANEL BLANK TOP			28	26
30" /32" / 36"	80"	4 PANEL COLONIAL TOP			28	26
30" /32" / 36"	80"	2 PANEL DESIGNER SERIES			28	26
30" /32" / 36"	80"	8 PANEL DESIGNER SERIES			28	26
30" /32" / 36"	80"	CRAFTSMAN DESIGN			28	26
SIDELITES						
12"/14"	80"	FLUSH	35	N/A	35	N/A
12"/14"	80"	2 PANEL REVERSE	35	N/A	35	N/A
8-0 HIGH PANELS						
30" /32" / 36"	80"	ALL DESIGNS	28	N/A	35	N/A
DOOR PANEL DIMENSIONS			OPTIONS			
PANEL WIDTH IS 1/4" UNDERSIZED			STANDARD HINGE PREP			
PANEL HEIGHT IS 79"			STANDARD LOCK PREP			
CUSTOM SIZING AVAILABLE WITH QUOTE			STANDARD LIGHT CUT OUT			

PRICING, CONDITIONS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE